



CAW-2004-0ME1

*Designed as a wall mount, this series can be used in a wide range of locations. Featuring non-corrosive aluminum construction, it is perfect for high volume cleaning and sanitizing jobs and is especially effective in factories, wash bays and food processing plants since there are no exhaust fumes.*

#### Pump:

Direct drive triplex piston General pump with ceramic plungers | Stainless-steel and brass trapping unloader | Forged brass manifold | Thermal relief valve | External quick connect low pressure detergent injector | Pump accepts incoming water up to 165°F (175°F on CAW-4004-0ME1)

#### Motor:

Industrial-duty totally enclosed fan-cooled electric motor with manual thermal overload protection | Low speed 1750 RPM | 4-foot power cord

#### Frame:

Aluminum base plate and frame | Aluminum wall mounting brackets | Aluminum hose and gun/wand holder

#### Components:

Time delay shutdown | Remote mounted electrical box included, must be mounted within 3½-feet of unit

#### Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x ¾-inch non-marking high pressure hose | Professional-grade insulated trigger gun with safety lock-off | Adjustable pressure insulated dual lance



# CAW Aluminum Series

## Cold Water – Electric – Wall Mount – Direct Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	UNLOADER	PLUG TYPE	LANCE	DIMENSIONS (LxWxH)*	SHIP WT.	NET WT.
CAW-2004-OME1	2000	3.9	6.0 HP, 230V, 1Ø, 24.1A	General	Factory preset	NEMA 6-30P	Adjustable, dual, 36in.	31x17.25x18in.	248 lb.	188 lb.
CAW-2004-OME3	2000	3.9	6.0 HP, 230V, 3Ø, 16.4A	General	Factory preset	NEMA L15-20P	Adjustable, dual, 36in.	31x17.25x18in.	223 lb.	163 lb.
CAW-3004-OME1	3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	General	Factory preset	NEMA 6-50P	Adjustable, dual, 36in.	31x17.25x18in.	268 lb.	208 lb.
CAW-3004-OME3	3000	3.9	8.0 HP, 230V, 3Ø, 22.8A	General	Factory preset	NEMA L15-30P	Adjustable, dual, 36in.	31x17.25x18in.	253 lb.	193 lb.
CAW-4004-OME1	4000	4.0	10.0 HP, 230V, 1Ø, 40.8A	General	Factory preset	NEMA 6-50P	Adjustable, dual, 48in.	34x18x19in.	368 lb.	293 lb.

\*Dimensions do not include the mounting brackets.

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0078	Remote box - Adds control box, may be mounted away from unit to control on/off	All models
CX-0109	Additional remotes, up to 3 qty. (Requires remote box option, CX-0078) - Additional remotes that may be added to the unit after the first remote is installed; requires remote box option CX-0078	All models
CX-0110	460V on 6.0 HP, 3Ø model - When 460V of power is available	CAW-2004-OME3
CX-0111	460V on 8.0 HP, 3Ø model - When 460V of power is available	CAW-3004-OME3
CX-0112	Auto start/stop - When trigger gun is released timer will turn unit off, when trigger gun is pulled, unit will restart	All models

### Accessory:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	All models



NEMA L15-20P,  
20-amp plug



NEMA 6-30P,  
30-amp plug



NEMA L15-30P,  
30-amp plug



NEMA 6-50P,  
50-amp plug

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).