

DHG Series — Direct/Belt Drive



DHG-4004-D0H6G
Direct Drive

Whether you choose the direct drive or the belt drive model, the 12V hot water gas pressure washer is capable of cleaning tough grime. Compact and completely portable, this series features a 12V Beckett burner and a 4-pancake bottom-fired heat exchanger.

Pump:

Direct or belt drive triplex piston General pump with ceramic plungers | Adjustable stainless-steel and brass unloader valve | Forged brass manifold | Thermal relief valve

Engine:

Performance-proven OHV engine with low-oil protection | 12V electric start — battery not included

Frame:

Reinforced powder coated steel tube frame with center balanced lifting hook | 15-inch pneumatic tires

Components:

½-inch schedule 80 pipe coil with 4-pancake bottom-fired heat exchanger | 12V Beckett burner | No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel) | Adjustable temperature | Hour meter

Miscellaneous:

Temperature rise 130°F/54°C above ambient | Water output temperature is 250°F in “wet” steam

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° | ¼-inch MEG and ¼-inch MQC wet steam nozzle — 25° | 50-foot x ½-inch steel wire-braided high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off | External downstream detergent injector with detergent nozzle



Portable Gasoline

Hot Water – DHG Series – Direct/Belt Drive

Direct Drive										
MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DHG-4004-D0H6G	4000	3.7	389cc Honda GX390 OHV	1.61 gallons	10.0 gallons	2.14 gph	299,600	57.5x35.5x59.5in.	601 lb.	478 lb.

Belt Drive										
MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DHG-4004-B0H6G	4000	3.7	389cc Honda GX390 OHV	1.61 gallons	10.0 gallons	2.14 gph	299,600	57.5x35.5x59.5in.	643 lb.	520 lb.

Options:

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0273	Stainless-steel coil wrap - Converts powder coated painted coil wrap to stainless-steel material	All models
HX-0278	Skid feet - Stationary applications	All models

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0195	Hose reel - 13-inch, 150-foot maximum hose length	All models
50-0196	Hose reel - 16-inch, 200-foot maximum hose length	All models



DHG-4004-B0H6G belt drive shown with stainless-steel coil wrap option, HX-0273

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.