

Skid Gasoline/ Diesel Dealer Hot Water Pressure Washers

HDS Series – Belt Drive

HDS-3505-0V6G

This hot water pressure washer is the machine professionals go to for the heaviest cleaning applications. It features a heavy-duty wraparound frame with stainless-steel panels for maximum durability. The removable front panel provides easy access for maintenance needs.

Pump:

Belt drive triplex piston General pump with ceramic plungers | Adjustable high pressure detergent injector

Engine:

Performance-proven OHV engine with low-oil protection or liquid-cooled Kubota diesel engine with electric start – battery not included

Frame:

Heavy-duty powder coated steel square tube skid frame Stainless-steel coil wrap, control panel and removable front panel

Components:

Horizontal schedule 80 pipe coil | 120V/15-amp auxiliary GFCI outlet | 2900-watt generator for efficient power to the burner and controls | No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel) | Three-way ball valve for inlet selection | Detergent and steam valves | Adjustable thermostat | Hour meter

Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° plus wet steam and fixed detergent nozzle | 50-foot x %-inch steel wire-braided high pressure hose (½-inch on HDS-3008 models) | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



US HydroTech Environmental Solutions | 5500 Commerce Blvd. Suite A, Rohnert Park, CA 94928 (707) 793-4800 | www.WaterForReuse.com | info@usHydroTech.com

Skid Gasoline/Diesel

Hot Water - HDS Series - Belt Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET W	
DS-3005-0V6G	3000	4.8	480cc Vanguard OHV	10.0 gallons	10.0 gallons	3.37 gph	471.800	50x34x46in.	854 lb.	750	
DS-3008-1H6G	3000	7.8	GX690 Honda OHV	10.0 gallons	10.0 gallons	3.67 gph	513,800	50x34x46in.	934 lb.	830	
DS-3008-0K6G	3000	7.8	725cc Kohler CH730 OHV	10.0 gallons	10.0 gallons	3.67 gph	513,800	50x34x46in.	934 lb.	854	
DS-3505-1H6G	3500	4.7	GX630 Honda OHV	10.0 gallons	10.0 gallons	3.37 gph	471.800	50x34x46in.	854 lb.	750	
DS-3505-0K6G	3500	4.7	624cc Kohler CH620 OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750	
DS-3505-0V6G	3500	4.7	627cc Vanguard OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750	
DS-3506-1H6G	3500	5.6	GX630 Honda OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750	
DS-3506-0K6G	3500	5.6	725cc Kohler CH730 OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750	
DS-4005-2H6G	4000	5.0	GX630 Honda OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750	
liesel Models	DCI	004		ENGINE FUEL	BURNER FUEL	BURNER FUEL	DTU ser have				
NODEL NUMBER	<i>PSI</i>	GPM	HORSEPOWER/ENGINE	TANK CAPACITY	TANK CAPACITY	CONSUMPTION	AT1 200	DIMENSIONS (LxWxH)	SHIP WT.	836	
DS-3006-0B7G DS-3008-0B7G	3000 3000	5.6 7.8	16.8 HP Kubota Z602 OHV 24.8 HP Kubota D902 OHV	10.0 gallons 10.0 gallons	10.0 gallons 10.0 gallons	3.37 gph 3.67 gph	471,800 513,800	56.5x34x46in. 56.5x34x46in.	940 lb. 940 lb.	836	
DS-3008-087G	4000	4.5	16.8 HP Kubota Z602 OHV	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb. 940 lb.	836	
	4000	4.0	10.0 HF Rubula 2002 0HV	10.0 galiolis	TO.0 Yalions	5.57 gph	471,000	30.3734740111.	940 ID.	000	
ptions: ART NUMBER	DESCRIPTIO	N/							FITS MODELS		
(-0100	300°F steam upgrade - Steam option lowers unit pressure to 350-PSI, 240°F rise above ambient with a maximum temperature of 300°F									HDS-3005-0V6G &	
X 0100	000 1 0104	in upgrau		50010 to 000 1 01, 2 10		Mar a maximum compo			HDS-3505 m		
X-0102	300°F steam upgrade - Steam option lowers unit pressure to 350-PSI, 240°F rise above ambient with a maximum temperature of 300°F								HDS-3006-0B7G & HDS-3506 models		
X-0147	Four point lifting capability - Allows unit to be lifted by crane								All models		
X-0149*	Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure								HDS-3006-0B7G & HDS-3506 models		
X-0150	Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas								HDS-3005-0V6G		
X-0151	Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas HDS-3505										
X-0152	Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas								HDS-3506 models		
X-0155	Trapping unloader - For hose runs longer than 50-feet and for cleaning elevated areas								HDS-3006-0B7G		
X-0197	All stainless-steel frame - Converts powder coated painted frame to stainless-steel material								All gasoline models		
X-0202	Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure								HDS-3008 models		
X-0203		Kohler engine upgrade - Higher performance 725cc Kohler CH730 OHV engine								HDS-3008-0K6G	
X-0227		Clutch drive pump - Stops the pump from spinning in bypass mode and helps extend the life of the pump; changes GPM to 4.3 when added to the unit							HDS-3005-0V6G		
X-0228		Clutch drive pump - Stops the pump from spinning in bypass mode and helps extend the life of the pump; changes GPM to 4.2 when added to the unit								HDS-3505 models	
K-0251	30-gallon steel diesel fuel tank - Supplies fuel to engine and burner								Diesel models		
X-0253	Pressure washer option for PWR-10-0ME1 trailer - mount package - Adds clutch drive pump option, larger 4.9 kW generator that is wired for burner, stain- less-steel heat exchanger shell and front panel and PWR-10-0ME1 with WX-0129 option								HDS-3505-1H6G		
X-0261	Clutch drive pump - Stops the pump from spinning in bypass mode and helps extend the life of the pump; standard flow rate								HDS-3005 & HDS-350 models		
X-0262	Clutch drive pump - Stops the pump from spinning in bypass mode and helps extend the life of the pump; standard flow rate								HDS-3506 models		
IX-0263	Clutch drive pump - Stops the pump from spinning in bypass mode and helps extend the life of the pump; standard flow rate								HDS-3008 & HDS-400 gasoline models		
									900000000000000000000000000000000000000	510	

*HX-0149 requires trapping unloader option HX-0152 or HX-0155

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
21-0313	Stainless-steel rain cap - Protects boiler from moisture build-up when unit is left outside	All models
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing	All models
AW-5740-0000	Wheel kit - Allows unit to become portable	All models
AW-6000-1007	Hot water skid equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant,	All models
	drawstrings to secure cover	

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.