

*Electric — Stationary — Belt Drive*



DC-2004-WSE2G

*This stationary pressure washer is constructed of stainless-steel to resist rust and corrosion, making it the perfect solution for wash bays to clean vehicles and equipment. Food and beverage facility owners use it to keep floors and worktables clean and sanitized.*

**Pump:**

Belt drive triplex piston General pump with ceramic plungers | Forged brass manifold | Thermal relief valve | Pump accepts incoming water up to 175°F | Quick connect low pressure detergent injector

**Frame:**

Stainless-steel cabinet design with removable panel | Four rubber isolators

**Motor:**

Totally enclosed fan-cooled electric motor with manual thermal overload protection (2000-PSI models) | Open drip-proof electric motor (1000 and 3000-PSI models) | 4-foot power cord with GFCI

**Component:**

Time delay shutdown

**Unit Includes:**

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x 3/8-inch non-marking high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



# Premium Series

## Cold Water – Electric – Stationary – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	UNLOADER	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-1003-WSE1G	1000	2.5	2.0 HP, 120V, 1Ø, 18.8A	Factory preset	NEMA 5-20P	29.5x20.5x15in.	222 lb.	172 lb.
DC-2004-WSE2G	2000	3.9	6.0 HP, 230V, 1Ø, 22.0A	Factory preset	NEMA 6-30P	29.5x20.5x15in.	272 lb.	214 lb.
DC-2004-WSE3G*	2000	3.9	6.0 HP, 230V, 3Ø, 15.0A	Factory preset	NEMA L15-20P	29.5x20.5x15in.	262 lb.	204 lb.
DC-3004-WSE3G*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A	Factory preset	NEMA L15-30P	29.5x20.5x15in.	292 lb.	234 lb.

\*460V motors available as options

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0069	<b>Auto start/stop</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models
CX-0076	<b>460V on 6.0-HP, 3-phase model</b> - For when you have 460V of power available	DC-2004-WSE3G
CX-0077	<b>460V on 8.0-HP, 3-phase model</b> - For when you have 460V of power available	DC-3004-WSE3G
CX-0078	<b>Remote box</b> - Adds control box which may be mounted away from unit to control on/off	All models
CX-0096	<b>Hour meter</b> - Displays the number of hours unit has been in operation	All models
CX-0109	<b>Additional remotes (up to 3)</b> - Additional remotes that may be added to unit after the first remote is installed	All models

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-9501-0000	<b>Stainless-steel wall mounting bracket</b> - Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0000	<b>Powder coated steel wall mounting bracket</b> - Provides a permanent location for your pressure washer in a shop or plant facility	All models
AW-9502-0001	<b>Powder coated steel floor stand</b> - Provides a permanent location for your pressure washer in a shop or plant facility	All models



NEMA 5-20P,  
20-amp plug



NEMA L15-20P,  
20-amp plug



NEMA 6-30P,  
30-amp plug



NEMA L15-30P,  
30-amp plug



DC-2004-WSE2G shown with  
stainless-steel wall mounting  
bracket, AW-9501-0000



Powder coated  
steel floor stand,  
AW-9502-0001

**WARNING: Cancer and Reproductive Harm** - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).